

Telephone:
Fax:
VAT Registration No.:

Notes			Specified value	Measured value
Vehicle identification				
No. of cylinders	Type	4/OHC		
Capacity (Fiscal)	cc	1994		
Compression ratio	:1	9,7		
Suitable for unleaded petrol		Yes		
Minimum octane rating	RON	95		
Ignition system	Make	Diamond		
Ignition system	Type	MPFI		
Ignition system	Description	Map-DIS		
Trigger location		Cam / Crankshaft		
Fuel system	Make	Subaru		
Fuel system	Type	MPFI		
Fuel system	Description	MFI-s		
Air metering	Type	Mass		
Combined ignition and fuel ECM		Yes		
Diagnostic socket		Yes		
Ignition system				
Ignition coil	Make	Diamond		
Ignition coil	Type	F-569-01R		
Ignition coil supply voltage	+ with ballast V	12		
Primary resistance	Ohm	0,62-0,76		
Secondary resistance	Ohm	17850-24150		
Firing order		1-3-2-4		
Tuning and emissions				
Ignition timing - basic BTDC	°Engine/rpm	15±10/800 Not adjustable		
Ignition timing - alternative	°Engine/rpm	AT=20±10/800		
Ignition advance checks	°Engine/rpm	ECM Controlled		
Idle speed	rpm	800±100 Not adjustable		
Idle speed - alternative	rpm	AC=850±100 Not adjustable		
Oil temperature for CO test	°C	80		
CO level at idle speed - tailpipe	Vol. % CO	0,5 Max Not adjustable		
HC level at idle speed	ppm	100		
CO2 level at idle speed	Vol. % CO2	14,5-16		
O2 level at idle speed	Vol. % O2	0,1-0,5		
Increased idle speed for CO test	rpm	2500-2800		
CO content at increased idle speed	Vol. %	0,2		
Lambda at increased idle	λ	0,98-1,02		
Spark plugs				
Spark plugs	Original equipment	NGK		
Spark plug	Type	BKR6E-11		
Electrode gap	mm	1,0-1,1		
Spark plugs	Make	Autolite		
Spark plug	Type	APP3922		

Manufacturer: Subaru

Model: Legacy (94-99) 2,0

© Autodata Limited 2008

Engine code: EJ20G

Output: 85 (110) 5600

3/15/10

Tuned for: R-Cat

Year: 1996-99

V7.412-ENGP440704

/Autodata

Electrode gap	mm	1,0	
Spark plugs	Make	Beru	
Spark plug	Type	14FR-7DUX	
Electrode gap	mm	1,1	
Spark plugs	Make	Bosch	
Spark plug	Type	FR7DCX	
Electrode gap	mm	1,1	
Spark plugs	Make	Champion	
Spark plug	Type	RC10YC4	
Electrode gap	mm	1,0-1,1	
Spark plugs	Make	NGK	
Spark plug	Type	BKR6E-11	
Electrode gap	mm	1,0-1,1	

Fuel system

System pressure	bar	2,35-2,65	
Regulated pressure with vacuum	bar	1,77-2,06	
Engine coolant temperature (ECT) sensor	Ohm/°C	350-390/80	
Crankshaft position (CKP) sensor/engine speed (RPM) sensor	Ohm	950-1250	
Injector	Ohm	11-12	
Injector opening duration (hot)	ms/rpm	2,1-3,5/-	
Idle air control (IAC) valve/idle speed control (ISC) actuator	Ohm	8-11	

Service checks and adjustments

Valve clearance -INLET	mm	0,18-0,22 cold	
Valve clearance -EXHAUST	mm	0,23-0,27 cold	
Compression pressure	bar	11-13	
Oil pressure	bar/rpm	2,9/5000	
Radiator cap	bar	0,9	
Thermostat opens	°C	76-80	

Lubricants and capacities

Engine oil options

Ambient temperature range		Cold climate	
Engine oil grade	SAE	5W/30	
Engine oil classification	API/ACEA	SJ/A2-96	
Ambient temperature range		Moderate climate	
Engine oil grade	SAE	10W/40	
Engine oil classification	API/ACEA	SJ/A2-96	
Ambient temperature range		Moderate climate alternative	
Engine oil grade	SAE	10W/30	
Engine oil classification	API/ACEA	SJ/A2-96	
Ambient temperature range		Hot climate	
Engine oil grade	SAE	20W/50	
Engine oil classification	API/ACEA	SJ/A2-96	
Engine with filter(s)	litres	4,5	

Other lubricants and capacities

Manual gearbox oil grade	SAE	75W/90	
Manual gearbox	litres	4,0	
Automatic transmission fluid	Type	Dexron II	
Differential oil grade - front	SAE	80W/90	
Differential front/AT	litres	1,2 (AT)	
Differential oil grade - rear	SAE	75W/90	
Differential rear	litres	0,8	
Cooling system	litres	6,0	
Brake fluid	Type	DOT 3/4	
Power steering fluid	Type	Dexron II	
Power steering fluid	litres	0,7	

Manufacturer: Subaru

Model: Legacy (94-99) 2,0

© Autodata Limited 2008

Engine code: EJ20G

Output: 85 (110) 5600

3/15/10

Tuned for: R-Cat

Year: 1996-99

V7.412-ENGP440704

/Autodata

Tightening torques				
9	Cylinder head instructions			
Cylinder head				
		Renew bolts	No	
Other engine tightening torques				
	Main bearings	Renew bolts/nuts	No	
20	Main bearings	Stage 1		
	Big end bearings	Renew bolts/nuts	No	
	Big end bearings	Stage 1	20 Nm	
	Big end bearings	Stage 2	45 Nm	
	Oil pump to cylinder block		6-7 Nm	
	Sump bolts		5 Nm	
	Sump drain bolt		44 Nm	
	Flywheel/driveplate		75 Nm	
	Clutch pressure plate		14-17 Nm	
	Crankshaft pulley/damper centre bolt		117-137 Nm	
	Camshaft sprocket/gear		73-83 Nm	
	Camshaft carrier/cap		12 Nm	
	Camshaft/rocker cover		6 Nm	
	Inlet manifold to cylinder head		25±2 Nm	
	Spark plugs		18-24 Nm	
	Crankshaft position (CKP) sensor/engine speed (RPM) sensor		7 Nm	
	Camshaft position (CMP) sensor		7 Nm	
	Engine coolant temperature (ECT) sensor		22-28 Nm	
	Lambda sensor (Oxygen)		18-24 Nm	
	Knock sensor (KS)		21-27 Nm	
	Engine oil pressure switch		22-28 Nm	
Chassis tightening torques				
	Front hub		166-206 Nm	
	Rear hub		166-206 Nm	
	Steering track rod end		78-88 Nm	
	Brake caliper to carrier	Front	37 Nm	
	Brake caliper carrier to hub	Front	78 Nm	
	Brake caliper to carrier	Rear	20 Nm	
	Brake caliper carrier to hub	Rear	50 Nm	
	Back plate to hub	Rear	46-58 Nm	
	ABS sensor	Front	32 Nm	
	ABS sensor	Rear	32 Nm	
	Road wheels		78-98 Nm	
Brake disc and drum dimensions				
	Minimum disc thickness - ventilated	Front	22 mm	
	Minimum disc thickness	Rear	8,5 mm	
	Disc runout	Front	0,075 mm	
	Maximum drum diameter	Rear	230,6 mm	
	Minimum pad thickness	Front	7,5 mm	
28	Minimum pad thickness	Rear	6,5 mm	
	Parking brake travel	No. of notches	7-8	
Air conditioning				
	Air conditioning refrigerant	Type	R134a	
36	Air conditioning refrigerant quantity	grams		
37	Air conditioning oil	Type		
35	Air conditioning oil quantity	cmi		

Autodata Note 9

Cylinder head bolts

Tighten in the following stages:

- 1) 29 Nm
- 2) 69 Nm
- 3) Slacken off 180°
- 4) Slacken off a further 180°
- 5) Bolts 1 & 2 = 34 Nm
- 6) Bolts 3-6 = 15 Nm
- 7) All bolts = 90°
- 8) All bolts = a further 90°.

Autodata Note 20

Main bearings

10 mm = 47±3 Nm
8 mm = 25±2 Nm
6 mm = 6,4 Nm.

Autodata Note 28

Minimum pad/shoe thickness

Measurement includes lining and pad/shoe backing plate.

Autodata Note 36

Refrigerant quantity

1994-95 = 600-700 grams
1996 RHD = 700-800 grams
1996 LHD = 600-700 grams
1997-99 RHD = 790-830 grams
1997-99 LHD = 550-650 grams.

Autodata Note 37

Oil type


1994-95 = ZXL 100 PG
1996 RHD = Dens Oil 9
1996 LHD = ZXL 200 PG
1997-99 RHD = Dens Oil 9
1997-99 LHD = ZXL 200 PG.

Autodata Note 35


Oil quantity

Refer to underbonnet label.


Cylinder layout



Timing mark



Timing mark



Tightening sequence

